




Huawei Mate 9 Battery Replacement

This guide shows how to replace the battery in your Huawei Mate 9.

Written By: Dominik Schnabelrauch



INTRODUCTION

Use this guide to replace the battery in your Huawei Mate 9 smartphone. When reassembling your phone apply new adhesive where it is necessary.

Before disassembling your phone, discharge the battery below 25%. The battery can catch fire and/or explode if accidentally punctured, but the chances of that happening are much lower if discharged.



TOOLS:


- [SIM Card Eject Tool](#) (1)
- [T2 Torx Screwdriver](#) (1)
- [iFixit Opening Tools](#) (1)
- [Spudger](#) (1)
- [Phillips #00 Screwdriver](#) (1)
- [Tweezers](#) (1)
- [iFixit Opening Picks set of 6](#) (1)



PARTS:

- [Huawei Mate 9 Replacement Battery](#) (1)
- [Stretch Release Battery Adhesive](#) (1)

Step 1 — Back Cover




- First switch off your phone and remove the SIM card tray.

Step 2




- Remove both screws on the bottom with a Torx T2 screwdriver.
 - Use a plastic opening tool to get between the display and the case. Open the smartphone by carefully prying out the display with all the parts out of the case.
- ⚠ Don't open the phone all the way, yet. The fingerprint sensor cable is still connected to the back cover.

Step 3



- Swing open the phone to the right side.
- Disconnect the fingerprint sensor cable with a spudger.

Step 4 — Battery Disconnect



- Carefully peel off the plastic sticker that holds both cables to the battery.

Step 5



- Remove the water indicator sticker and the Phillips #00 screw beneath it, that holds the cable bracket in its place.

Step 6




- Remove the cable bracket.

Step 7




- Use a spudger to disconnect the interconnect, the battery and the display flex cable.

Step 8 — Battery



- Peel out the adhesive strip which is placed beneath the battery by steadily pulling at the tab in a flat angle.
- ❗ If the adhesive strip breaks, grab and twist it around tweezer tips a couple of times and then continue.

Step 9



- If the battery is not freed, use an opening pick to pry under the battery, freeing it from the remaining adhesive.
- Remove the battery.
- ✦ When reassembling your phone, replace old adhesive with [stretch release adhesive strips](#), [double-sided tape](#), or [pre-cut adhesive strips](#).
- ⚠ Never reinstall a battery that has been bent or damaged during removal.

To reassemble your device, follow these instructions in reverse order. When reassembling your phone apply new adhesive where it is necessary.