




# Solio CLASSIC2 LED Light Replacement

This guide will help you effectively replace the LED light

Written By: Eric Padilla



---

## INTRODUCTION

The LED Lights shows if the device you are charging is charged and if the CLASSIC2 is charging itself. Replacing the LED lights requires soldering. If needed guides on soldering are found on iFixit's website. [How To Solder and Desolder Connections](#)



### TOOLS:

- [Soldering Workstation](#) (1)
  - [Phillips #1 Screwdriver](#) (1)
  - [iFixit Opening Tools](#) (1)
  - [Tweezers](#) (1)
-

## Step 1 — Disconnecting the Battery




- Turn off the device by pressing on the clear power button behind the device.
- ① To make sure that it is off, make sure the button is not flashing green.

## Step 2




- Using the Phillips #1 screwdriver, remove the 2mm screw located on the bottom of the device, near the hinge.

### Step 3



- Using the plastic opening tools, gently pry open the side of the large panel.
- Keeping the tool in, slowly slide the tool along the side of the panel.


### Step 4




- Rotate the device 180 degrees.
- ⓘ Make sure the opening on other side of the device does not snap closed.
- Gently slide the plastic opening tool along the side of the panel.




## Step 5



 Do not fully pull apart the back panel from the device. Doing so can rip the two red and blue wires attached to the panel.


- Using both hands, slowly pull apart the back panel from the rest of the device.
- Gently flip the back panel open so the circuit board faces up and the two panels are side by side.

## Step 6




- Softly pinch the red and blue wires close to the white connector.
- To pull the wires out, wiggle them back and forth until the connector is fully out.

## Step 7 — Circuit Board




- Unscrew the three 2mm screws holding the circuit board down using a Phillips #1 screwdriver.


## Step 8



- Make sure the white USB port cover on the side of the device is pulled out or you won't be able to lift the circuit board.
- Gently lift the circuit board out of the device using tweezers.

## Step 9 — LED Light



-  Soldering can melt key components and cause harm to both the user and the device. Read soldering

---

guide before attemptingDesolder the LED lights.

- Desolder the LED lights.
- 

To reassemble your device, follow these instructions in reverse order.