

JIAYU F1 Volume Button Replacement

This guide will provide instructions on how to...

Written By: Nicole



INTRODUCTION

This guide will provide instructions on how to replace the volume button.

TOOLS:

iFixit Opening Tool (1)
Precision Tweezers Set (1)
Phillips #00 Screwdriver (1)

Step 1 — Turn Off the Phone



 Turn the phone off by holding down the power button located on the top of the phone.

Step 2 — Remove the Back Case







- Find the small indentation at the bottom right of the phone and pry open the back case of the phone using your fingernail or small plastic opening tool.
- Gently remove the back case completely from the phone.

Step 3 — Remove the Battery








- Insert a fingernail or the small plastic opening tool into the recess in the bottom center of the battery and lift upward.
- Remove the battery from the phone.
- *When replacing the battery, align the copper ports on the top right of the battery with the corresponding ports in the battery cavity.*

Step 4 — Remove the Interior Midframe Assembly







- With the phone lying face down, remove the nine 3 mm Phillips # 00 screws from the midframe.
- Gently run a plastic opening tool down along the left and right sides of the phone to separate the black midframe assembly from the silver display casing.
- Carefully remove the midframe assembly from the display casing by pulling up and away from the phone.

Step 5 — Remove Volume Button







- Locate the silver volume button on the side of the phone.
- Use the precision <u>tweezers</u> to slide the volume button out of the groove.
- *When replacing the volume button align the flat side of the button to the silver edge of the display with the rounded edge facing the black frame.*

To reassemble your device, follow these instructions in reverse order.